

Declares that the product:

Reference:

MB420

Placed on the market as Model(s):

**ONE410
ONE420
ONE425**

**1322
1623**

LBB14X

Conforms to essential requirements and relevant provisions of following European Directives provided that it is installed, maintained and used in the application for which it is intended for, with respect of the "professional practices", relevant installation standards and manufacturer's instructions:

Directive 2014/53/EU	Radio Equipment (RED)
Directive 2014/35/EU	Low Voltage (LVD)
Directive 2014/30/EU	Electromagnetic compatibility (EMCD)
Directive 2011/65/EU amended by Directives (EU) 2015/863 + 2017/2102	Restriction of the use of certain hazardous substances (RoHS)
Directive 2009/125/EC	Ecodesign (ERP)

Standard(s) used to show compliance when applicable:

Safety (Art. 3.1a)	EN 60950-1	2006 +A11 +A1 +A12 +A2	(LVD) - ITE Safety
	EN 62311	2008	(LVD) - EMF
EMC (Art. 3.1b)	EN 55032	2012+AC	(EMCD) - MME Emissions
	EN 55035	2017	(EMCD) - MME Immunity
	EN 301 489-1	V1.9.2	(EMCD) - Radio Common
	EN 301 489-17	V2.2.1 (*)	(EMCD) - Wi-Fi 2,4GHz, 5GHz
Radio Spectrum (Art. 3.2)	EN 300 328	V2.1.1	(RED) - Wi-Fi 2,4GHz
	EN 301 893	V2.1.1	(RED) - Wi-Fi 5GHz
	EN 302 502	V2.1.1	(RED) - Wi-Fi 5GHz DFS
Various	EN 50581	2012	(RoHS)
	(EC) No 2019/1782	2019	(ERP) - External PSU
	(EC) No 1275/2008	2008	(ERP) - Stby & Off mode
	(EC) No 801/2013	2013	(ERP) - Stby & Off mode

* This standard hasn't yet been published on EU OJ Harmonized Standard list of related EU Directive

Place and date of issue: Leuven, Belgium, 20 January 2020



ekinops
Philippe Moulin
Chief Operating Officer

Name, function: Philippe Moulin, COO

Annex to EU Declaration of Conformity

Regulation 801/2013 (Standby & Off-mode, Network Standby)

Reference of product	MB420		
Model(s) of product	ONE410 ONE420 ONE425	1322 1623	LBB14X
Class of product (acc. to Annex II 9(b))	Networked Equipment. According to EC Regulation 801/2013, the concept 'Network Port' is not applicable to the above referenced product, as it is not able to remotely be activated through any of its Network interfaces (none of the Network interface has wake-on functionality).		
Power management functionality Off / Standby mode (acc. to Annex II 9(d))	Inappropriate for intended use of equipment. Technical justification : - Equipment that deliver network access with bandwidth and 100% availability SLA committed by the operators to their end customers. - PABX functionalities (Remote Power Feeding/FXS/BRI/PRI) and router functionalities (including transport of wake-on trigger) must be permanently available for downstream equipment.		
Guide for activation / de-activation of the wireless network port (acc. to Annex II 7(c))	User can enable/disable Wi-Fi port via a configuration interface. Wi-Fi port is disabled by default.		