

Declares that the product:

Reference:

MB250

Placed on the market as Model(s):

ONE521M

LBB250

Conforms to essential requirements and relevant provisions of following European Directives provided that it is installed, maintained and used in the application for which it is intended for, with respect of the “professional practices”, relevant installation standards and manufacturer’s instructions:

Directive 2014/53/EU	Radio Equipment (RED)
Directive 2011/65/EU amended by Directives (EU) 2015/863 + 2017/2102	Restriction of the use of certain hazardous substances (RoHS)
Directive 2009/125/EC	Ecodesign for Energy-Related Products (ERP)

Standard(s) used to show compliance when applicable:

Safety (Art. 3.1a)	EN 62368-1 EN 62311	2014 +AC +A11 2008	MME Safety EMF
EMC (Art. 3.1b)	EN 55032 EN 55035 ETSI EN 301 489-1 Draft ETSI EN 301 489-17 ETSI EN 301 489-52	2015 +A11 2017 +A11 V1.9.2 V2.2.1 (*) V1.2.1	MME Emissions MME Immunity Radio Common Wi-Fi 2,4GHz, 5GHz Digital Cellular
Radio Spectrum (Art. 3.2)	ETSI EN 300 328 ETSI EN 301 893 ETSI EN 302 502 ETSI EN 301 511 ETSI EN 301 908-1 ETSI EN 301 908-2 ETSI EN 301 908-13	V2.2.2 V2.1.1 V2.1.1 V12.5.1 V13.1.1 V13.1.1 V13.1.1	Wi-Fi 2,4GHz Wi-Fi 5GHz Wi-Fi 5GHz DFS GSM, EDGE, GPRS Radio Common UMTS, UTRA LTE, E-UTRA
Various	EN 63000 (EU) No 2019/1782 (EC) No 1275/2008 (EU) No 801/2013	2018 2019 2008 2013	(RoHS) (ERP) - External PSU (ERP) - Stby & Off mode (ERP) - Stby & Off mode
* This standard hasn't yet been published on EU OJ Harmonized Standard list of related EU Directive			

Annex to EU Declaration of Conformity

(EU) Commission Regulation 801/2013 (Standby & Off-mode, Network Standby)

Reference of product	MB250				
Model(s) of product	ONE521M	LBB250			
Class of product (acc. to Annex II 9(b))	Networked Equipment. According to (EU) Commission Regulation 801/2013, the concept 'Network Port' is not applicable to the above referenced product, as it is not able to remotely be activated through any of its Network interfaces (none of the Network interface has wake-on functionality).				
Power management functionality Off / Standby mode (acc. to Annex II 9(d))	Inappropriate for intended use of equipment. Technical justification : - Equipment that deliver network access with bandwidth and 100% availability SLA committed by the operators to their end customers. - PABX functionalities (Remote Power Feeding/FXS/BRI/PRI whenever featured) and/or router functionalities (including transport of wake-on trigger) must be permanently available for downstream equipment.				
Guide for activation / de-activation of the wireless network port (acc. to Annex II 7(c))	User can enable/disable Wi-Fi port via a configuration interface. Wi-Fi port is by default disabled.				

